


## Check valves



### TECHNICAL REQUIREMENT

1. Before assembling, all parts should be clean, no oil or grease, remove all burrs and sharp edges.
2. Before connecting, body cap male thread should be coated with sealing glue.

NO.	Name	Material
1	Body	Brass
2	Spring	Stainless steel
3	Disc	Plastic
4	Gasket	EPDM
5	Body end	Brass

Check valve
Size 1/2"
3/4"
1"
1 1/4"
1 1/2"
2"
2 1/2"

G	L	D	H
1/2"	12.5	33	46
3/4"	13.5	38	51
1"	14	44	53
1-1/4"	15	59	61
1-1/2"	18	67	70
2"	18.5	80	78
2-1/2"	23	93	103



Check valve
Size 1/2"
3/4"
1"
1 1/4"
1 1/2"
2"
2 1/2"



Check valve
Size 1/2"
3/4"
1"

## Check valve & filter valves & gate valves



Check valve with stainless steel filter
Size 1/2"
3/4"
1"
1 1/4"
1 1/2"
2"
2 1/2"



Stainless steel filter
Size 1/2"
3/4"
1"
1 1/4"
1 1/2"
2"
2 1/2"



Filter valve
Size 1/2"
3/4"
1"



Filter valve
Size 1/2"
3/4"
1"



Filter valve
Size 1/2"
3/4"
1"



Swing valve
Size 1/2"
3/4"
1"



Gate valve
Size 1/2"
3/4"
1"
1-1/4"
1-1/2"
2"



Gate valve
Size 1/2"
3/4"
1"
1-1/4"
1-1/2"
2"